

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 April 2003 (10.04.2003)

PCT

(10) International Publication Number  
**WO 03/029973 A1**

(51) International Patent Classification<sup>7</sup>: **G06F 9/46, 9/54**

(21) International Application Number: PCT/EP02/09387

(22) International Filing Date: 22 August 2002 (22.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
01123052.1 26 September 2001 (26.09.2001) EP

(71) Applicant (for all designated States except US): **SAP AK-  
TIENGESELLSCHAFT** [DE/DE]; Neurotstr. 16, 69190  
Walldorf (DE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PFEIFER, Wolfgang**  
[DE/DE]; Schwetzingen, Str. 44, 69168 Wiesloch (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CIL, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: INTERACTION BETWEEN COMPUTERS WITH DIFFERENT OBJECT-ORIENTED RUN-TIME ENVIRON-  
MENTS



(57) Abstract: First and second computers (901, 902) operate in first and second object-oriented run-time environments with first and second applications (201, 202) and corresponding objects (A1/A2, B1/B2, C1/C2). Initiated by a communicator (101) and supported by a network (990), the first computer (901) sends a message (GET 111, SET 121, INSTRUCT 131) with object and action identification to the second computer (902). The second computer (902) uses an interpreter (102) to identify an object (A2, 152) in the second run-time environment according to the object identification. The interpreter (102) further verifies the existence of the identified action for the object (A2, 152) in the second run-time environment and determines (403) a representation of the action in the second run-time environment for the identified object (A2, 156). The interpreter (102) then executes the action by using the representation. Thereby, the interpreter (102) calls operations and methods of the identified object (A2, 156).

WO 03/029973 A1

INTERACTION BETWEEN COMPUTERS WITH DIFFERENT OBJECT-ORIENTED  
RUN-TIME ENVIRONMENTS

Field of the Invention

- 01 The present invention generally relates to data processing and, more particularly, relates to computer systems, computer programs, and methods to use properties and method of objects in computer business applications.

Background of the Invention

- 02 Computer applications often use object-oriented programming techniques. In the applications, objects are data structures with properties and methods. For convenience of explanation, the term "function" is used instead so that an object has properties and functions.
- 03 The objects are often arranged in hierarchy. Reading ("GET") and modifying ("SET") a property or executing a function ("INSTRUCT") requires identification (ID) of the object within the hierarchy, for example, by an object name. Technically, each object operates in a run-time environment, that means in a predefined technical format for the object ("object model"). For example, (a) the ID is a string with a predetermined number of characters and (b) an output value is an integer.
- 04 Multiple applications are often linked in a network so that using a single run-time environment is often impossible. When first and second computer applications operate in different first and second

run-time environments, they conveniently use similar objects with similar properties and functions.

- 05 However, similarity alone does not guarantee technical compatibility. Translation software between the applications is required as well. Linking the application by communication middleware is well known in the art. Middleware is commercially available, such as for example, COM, DCOM, and CORBA.
- 06 For example, a first run-time environment (provider) needs to communicate with an identified object in a second run-time environment (consumer). Such communication often involves multiple hierarchy levels of objects. Going through multiple hierarchy levels by both environments technically causes network load and delays.
- 07 There is an ongoing need to provide improved inter-run-time communication means so that some or all of the above disadvantages are mitigated.

#### Summary of the Invention

- 08 The present invention relates to a method for communication between a first computer operating in a first object-oriented run-time environment and a second computer operating in a second, different object-oriented run-time environment. The first run-time environment accesses a property or a function of an object, hereinafter "action", in the second run-time environment. The first computer sends a first message with object identification and action identification to the second computer and causes the second computer to perform the following steps: identifying the object in the second run-time environment according to the object identification;

verifying the existence of the action in the identified object in the second run-time environment; determining a representation of the action in the second run-time environment for the identified object; and executing the action by using the representation, thereby returning a second message to the first computer as confirmation message to the first computer, the second message with object identification and response identification, executing with (a) converting a request identification that is part of the action identification to a further representation for the second run-time environment by looking up in a table; and (b) inserting the further representation into the second application.

- 09 While identifying, interaction between the computers is not required; and execution is technically independent from the first run-time environment, since only the second run-time environment has to be used.
- 010 The invention also relates to a computer program product and to a communication system that implement the method.

#### Brief Description of the Drawings

- 011 FIG. 1 illustrates a simplified block diagram of a computer network system having a plurality of computers;
- 012 FIG. 2 illustrates a simplified block diagram of first and second computers with first and second applications, in first and second run-time environments, respectively, that communicate according to the present invention;

- 013 FIG. 3 illustrates messages from the first computer to the second computer;
- 014 FIG. 4 illustrates messages from the second computer to the first computer;
- 015 FIG. 5 illustrates an object in the second application on the second computer;
- 016 FIG. 6 illustrates a conversion table in the second application on the second computer;
- 017 FIG. 7 illustrates a flowchart diagram for a method of the present invention in general; and
- 018 FIG. 8 illustrates flowchart diagrams for the method of FIG. 7 for first, second and third embodiments.

#### Computer System in General

- 019 FIG. 1 illustrates a simplified block diagram of exemplary computer system 999 having a plurality of computers 900, 901, 902 (or even more).
- 020 Computer 900 can communicate with computers 901 and 902 over network 990. Computer 900 has processor 910, memory 920, bus 930, and, optionally, input device 940 and output device 950 (I/O devices, user interface 960). As illustrated, the invention is implemented by computer program product 100 (CPP), carrier 970 and signal 980.
- 021 In respect to computer 900, computer 901/902 is sometimes referred to as "remote computer", computer 901/902 is, for example, a server, a peer device or other common network node, and typically has many or all of the elements described relative to computer 900.

- 022 Computer 900 is, for example, a conventional personal computer (PC), a desktop device or a hand-held device, a multiprocessor computer, a pen computer, a microprocessor-based or programmable consumer electronics device, a minicomputer, a mainframe computer, a personal mobile computing device, a mobile phone, a portable or stationary personal computer, a palmtop computer or the like.
- 023 Processor 910 is, for example, a central processing unit (CPU), a micro-controller unit (MCU), digital signal processor (DSP), or the like.
- 024 Memory 920 is elements that temporarily or permanently store data and instructions. Although memory 920 is illustrated as part of computer 900, memory can also be implemented in network 990, in computers 901/902 and in processor 910 itself (e.g., cache, register), or elsewhere. Memory 920 can be a read only memory (ROM), a random access memory (RAM), or a memory with other access options. Memory 920 is physically implemented by computer-readable media, for example: (a) magnetic media, like a hard disk, a floppy disk, or other magnetic disk, a tape, a cassette tape; (b) optical media, like optical disk (CD-ROM, digital versatile disk - DVD); (c) semiconductor media, like DRAM, SRAM, EPROM, EEPROM, memory stick.
- 025 Optionally, memory 920 is distributed. Portions of memory 920 can be removable or non-removable. For reading from media and for writing in media, computer 900 uses well-known devices, for example, disk drives, or tape drives.

- 026 Memory 920 stores modules such as, for example, a basic input output system (BIOS), an operating system (OS), a program library, a compiler, an interpreter, and a text- processing tool. Modules are commercially available and can be installed on computer 900. For simplicity, these modules are not illustrated.
- 027 CPP 100 has program instructions and - optionally - data that cause processor 910 to execute method steps of the present invention. In other words, CPP 100 can control the operation of computer 900 and its interaction in network system 999 so that it operates to perform in accordance with the invention. For example and without the intention to be limiting, CPP 100 can be available as source code in any programming language, and as object code ("binary code") in a compiled form.
- 028 Although CPP 100 is illustrated as being stored in memory 920, CPP 100 can be located elsewhere. CPP 100 can also be embodied in carrier 970.
- 029 Carrier 970 is illustrated outside computer 900. For communicating CPP 100 to computer 900, carrier 970 is conveniently inserted into input device 940. Carrier 970 is implemented as any computer readable medium, such as a medium largely explained above (cf. memory 920). Generally, carrier 970 is an article of manufacture having a computer readable medium with computer readable program code to cause the computer to perform methods of the present invention. Further, signal 980 can also embody computer program product 100.

- 030 Having described CPP 100, carrier 970, and signal 980 in connection with computer 900 is convenient. Optionally, further carriers and further signals embody computer program products (CPP) to be executed by further processors in computers 901 and 902.
- 031 Input device 940 provides data and instructions for processing by computer 900. Device 940 can be a keyboard, a pointing device (e.g., mouse, trackball, cursor direction keys), microphone, joystick, game pad, scanner, or disc drive. Although the examples are devices with human interaction, device 940 can also be a device without human interaction, for example, a wireless receiver (e.g., with satellite dish or terrestrial antenna), a sensor (e.g., a thermometer), a counter (e.g., a goods counter in a factory). Input device 940 can serve to read carrier 970.
- 032 Output device 950 presents instructions and data that have been processed. For example, this can be a monitor or a display, (cathode ray tube (CRT), flat panel display, liquid crystal display (LCD), speaker, printer, plotter, vibration alert device. Output device 950 can communicate with the user, but it can also communicate with further computers.
- 033 Input device 940 and output device 950 can be combined to a single device. Any device 940 and 950 can be provided optional.



- 034 Bus 930 and network 990 provide logical and physical connections by conveying instruction and data signals. While connections inside computer 900 are conveniently referred to as "bus 930", connections between computers 900-902 are referred to as "network 990". Optionally, network 990 includes gateways which are computers that specialize in data transmission and protocol conversion.
- 035 Devices 940 and 950 are coupled to computer 900 by bus 930 (as illustrated) or by network 990 (optional). While the signals inside computer 900 are mostly electrical signals, the signals in network are electrical, electromagnetic, optical or wireless (radio) signals.
- 036 Networks are commonplace in offices, enterprise-wide computer networks, intranets and the Internet (e.g., world wide web). Network 990 can be a wired or a wireless network. To name a few network implementations, network 990 can be, for example, a local area network (LAN), a wide area network (WAN), a public switched telephone network (PSTN); a Integrated Services Digital Network (ISDN), an infrared (IR) link, a radio link, like Universal Mobile Telecommunications System (UMTS), Global System for Mobile Communication (GSM), Code Division Multiple Access (CDMA), or satellite link.

- 037 A variety of transmission protocols, data formats and conventions is known, for example, as transmission control protocol/internet protocol (TCP/IP), hypertext transfer protocol (HTTP), secure HTTP, wireless application protocol (WAP), unique resource locator (URL), a unique resource identifier (URI), hypertext markup language (HTML), extensible markup language (XML), extensible hypertext markup language (XHTML), wireless markup language (WML), Standard Generalized Markup Language (SGML).
- 038 Interfaces coupled between the elements are also well known in the art. For simplicity, interfaces are not illustrated. An interface can be, for example, a serial port interface, a parallel port interface, a game port, a universal serial bus (USB) interface, an internal or external modem, a video adapter, or a sound card.
- 039 Computer and program are closely related. As used hereinafter, phrases, such as "the computer provides" and "the program provides", are convenient abbreviation to express actions by a computer that is controlled by a program.

#### Detailed Description of the Invention

- 040 For convenience, a list of references is provided prior to the claims.
- 041 FIG. 2 illustrates a simplified block diagram of first computer 901 and second computer 902 that communicate according to the present invention. Computers 901 and 902 perform applications 201 and 202, in first and second run-time environments, respectively.

Application 201 operates in a first run-time environment that has a first object model; application 202 operates in a second, different run-time environment that has a second object model. Objects A1, B1 and C1 in application 201 correspond to objects A2, B2 and C2 in application 202. FIG. 2 illustrates this mapping by dotted lines. For explanation, distinguishing the letters A, B and C provides sufficient object identification. Indices 1 and 2 conveniently distinguish the computers. Object A2 is explained with more detail in FIG. 5 (reference 152).

042 In operation, computers 901 and 902 preferably visualize their performance on screens 951 and 952 to first and second users, respectively. For example, screen 951 on computer 901 shows representations obtained from computer 902 (cf. FIG. 4, 118, 128, 138). Both users are mentioned here only for convenience of explanation; the present invention does not require them to be involved.

043 Network 990 (cf. FIG. 1) is the infrastructure to convey information between computers 901 and 902 in both directions. In both computers, first and second run-time environments cooperate with each other, preferably, by sending messages through network 990. The messages are convenient for explanation, but not essential for the present invention. In the alternative, the communication is performed by computer middleware, such as COM or CORBA, well known in the art and not further illustrated.

044 Communicator 101 operates on computer 901 as a message generator and sends messages GET 111, SET 121, INSTRUCT 131 to computer 902 (arrows to the right). As explained in connection with FIG. 3, the

messages carry object identification and action identification.

045 Interpreter 102 (i.e. CPP) operates on computer 902 as message interpreter according to a method of the present invention (cf. FIG. 4). Interpreter 102 sends messages RESULT 112, CONFIRM 122, FEEDBACK 132 and ERROR 192 to computer 901. Es explained in connection with FIG. 4, the messages carry object ID and response ID. It is an advantage of the present invention that the response ID has representations of object properties and object functions suitable for the first run-time environment of computer 901. As mentioned, the representations can be shown on screen.

046 There is no need to use all messages that are illustrated in FIG. 2. Preferably, the messages are exchanged as paired messages (the first message from computer 901, the second messages from computer 902), each pair for an embodiment of the present invention (GET/RESULT, SET/CONFIRM and INSTRUCT/FEEDBACK).

047 The first embodiment relates to the action of reading (GET) a property of an object (A) und uses messages GET 111 and RESULT 112. The second embodiment relates to the action of modifying (SET) a property of the object (A) and uses messages SET 121 and CONFIRM 122. The third embodiment relates to the action of executing (INSTRUCT) a function of the object (A) and uses messages INSTRUCT 131 and FEEDBACK 132. Error message 192 from computer 902 to computer 902 is optionally used in all embodiments.

048 An exemplary scenario relates to the automotive industry. A customer ("first user") uses first application 201 to customize a car; a technician

("second user") in a factory uses second application 202 to response to the customer. Software objects correspond to hardware components; objects A, B and C correspond to cars ALPHA, BETA, and GAMMA, respectively (not shown). Applications 201 and 202 communicate with their users in first ° and second °° natural languages (e.g., German and Spanish). To conveniently describe the invention in a single language, symbols ° and °° distinguish first and second natural languages, respectively. For example, "green °" stands for the German word "grün" and "green °°" stands for the Spanish word "verde", both in the same meaning of green color. In a real implementation, these superscripts are not shown.

049 For convenience of explanation, the example scenario further assumes consecutive execution of the embodiments. The customer for ALPHA

- first, asks for the color ("GREEN °"),
- second, changes the color ("to RED °"), and
- third, communicates with applications 201 and 202 to check volume ("LITER °") and price ("EURO") for a desired color type ("METALLIC °").

050 FIG. 3 illustrates messages GET 111, SET 121 and INSTRUCT 131 from computer 901 to computer 902 (cf. FIG. 2, arrows to the right). The messages comprise object identification (ID) 115, 125 or 135 (e.g., object A) and action identification (ID) 116/117, 126/127, or 136/137. For first or second embodiments, the action ID comprises property ID 116 or 126 and request ID 117 or 127. For the third embodiment, the action ID comprises function ID 136 and parameter ID 137 (parameter representation).

051 FIG. 4 illustrates messages RESULT 112, CONFIRM 122, and FEEDBACK 132 from computer 902 to computer 901 (cf. FIG. 2, arrows to the left). The messages comprise object ID 115, 125 or 135 (e.g., object A, as in FIG. 3) and response ID 116/118 or 126/128 or 136/138.

For first or second embodiments, the response ID comprises property ID 116 or 126 (as in FIG. 3) and property representation 118 or 128. Property representation is that of first run-time environment in computer 901.

For the third embodiment, the response ID comprises function ID 136 (as in FIG. 3) and parameter representation 138. Function and parameter representation are suitable to first run-time environment of computer 901.

052 The messages in FIGS. 3-4 are now explained in connection with the embodiments. So far, error messages 192 are neglected.

053 In the first embodiment, the customer needs to know the color of the car ALPHA. Application 201 uses object A1 and communicator 101 to send GET 111 with object ID 115 "A", property ID 116 "COLOR", and request ID 117 "GET COLOR" (action).

054 At computer 902, interpreter 102 executes a method (cf. 410 in FIG. 8) in combination with corresponding object A2 (of application 202) and returns RESULT 112 with corresponding object ID 115 and property ID 116, but with property representation 118 "COLOR GREEN °" (response). Representation 118 is in the suitable format for application 201. Application 201 now indicates "Green ° to the customer (e.g. on screen 951).

055 The role of user of application 202 is optional. When executing the method, interpreter 102 converts representations to and from the different run-time environments. It is convenient (but not necessary) that application 202 shows the color to the technician in the second language °° or invites the technician to input the color in this second language °°.

056 In the second embodiment, the customer wishes to set the color of the car ALPHA to "red". Application 201 uses object A1 and communicator 101 to send SET 121 to application 202 with object ID 125 "A", property ID 126 "COLOR", and request ID 127 "SET TO RED °°".

057 At computer 902, interpreter 102 executes a method (cf. 420 in FIG. 8) in combination with corresponding object A2 (of application 202) and returns CONFIRM 122 to application 201 with corresponding object ID 125 and property ID 126, but with property representation 128 "YES, SET TO RED °°".

058 In the third embodiment, the customer communicates with applications 201 and 202 to check price and volume for a desired color type. Application 201 again uses object A1 and communicator 101 to send INSTRUCT 131 to application 202 with function ID 136 "CALCULATE" and parameter ID 137 "COLOR TYPE ° = METALLIC °", "VOLUME ° = X", "PRICE ° = Y". The parameters are input parameter (COLOR TYPE) and output parameters (VOLUME, PRICE).

059 At computer 902, interpreter 102 executes the method in combination with corresponding object A2. Interpreter identifies object A2, verifies the parameters of A2, determines parameter

representations, converts representations to the second-run time environment, triggers application 202 to execute the calculations, converts the calculation results X °° and Y °° to representations for the first run-time environment, and returns FEEDBACK 132 that indicates the output parameters (X °° and Y °°) as numeric values.

060 Before explaining the methods, details for the software at computer 902 are given.

061 FIG. 5 illustrates object 152 (A2) in application 202 of second computer 902. Object A2 has property COLOR. COLOR has a plurality of property representations 162 (RED °°, YELLOW °°, and GREEN °°) in the second run-time environment. In the example of FIG. 5, COLOR is represented by strings in the second natural language (°°). One representation of COLOR is being selected (e.g. GREEN °°). For the third embodiment, object A2 also has function 172 CALCULATE with parameters COLOR TYPE, VOLUME, and PRICE.

062 FIG. 6 illustrates conversion table 182 (mapping table) in application 202 (optionally in interpreter 102) on computer 902. Due to different run-time environments in computers 901 and 902, properties and functions of corresponding objects are represented differently. Table 182 illustrates property representations 161 and 162. According to the present invention, interpreter 102 on computer 902 converts representations 161 from the format of the first run-time environment (RTE) to representations 162 (cf. FIG. 5) in the format of the second run-time environment and vice versa. As an example, table 182



converts string representations in the first language (°) of the property COLOR to a string representation in the second language (°°). Again, using natural languages is convenient for explanation; in practice there is great variety of conversion between different object models, such as integer-to-real number conversion; string-to-string conversion; one-byte character representation (e.g., ASCII) to double-byte representation (e.g., unicode), etc.

063 Persons of skill in the art can provide further property conversion means, for example: string-to-integer, integer-to-real, 4-byte-integer to 8-byte-integer, etc. and vice versa. Table 182 illustrates property representations only; function conversion including parameter conversion is likewise to the property conversion, persons of skill in the art can accomplish this without the need of further explanation herein.

064 FIG. 7 illustrates flowchart diagrams for method 400 of the present invention, with method 400 being a generalization for all embodiments.

065 FIG. 8 illustrates flowchart diagrams for the embodiments: first method 410, second method 420 and third method 430.

066 Generally, method 400 relates to communication between first computer 901 operating in a first object-oriented run-time environment and second computer 902 operating in a second, different object-oriented run-time environment, wherein computer 901 sends message (GET 111, SET 121, or INSTRUCT 131) with object ID 115, 125, 135 and action ID 116/117,

126/127 or 136/137 to second computer 902 and causes second computer 902 to perform the method steps identify 401, verify 402, determine 403, and execute 405, 404, 406, 407. The method steps are performed by interpreter 102 in combination with application 202 after computer 902 has received message 111, 121, or 131.

067 In step identifying 401 an object in the second run-time environment according to object ID 115, 125, 135, interpreter 102 identifies the corresponding object in application 202 by evaluating the object ID of the message. Step 401 is likewise for all embodiments, i.e. steps 411, 421, and 431. In the example scenario, with object ID "A", the object is A2 (cf. FIG. 5).

068 In step verifying 402, interpreter 102 verifies the existence of the action in the identified object in the second run-time environment. In the first and second embodiments, steps 412 and 422, interpreter evaluates action identifier 116 and 126 and determines existence or non-existence of PROPERTY COLOR. In case of non-existence, interpreter 102 issues error message 192 (cf. FIG. 2). In the third embodiment, step 432, interpreter evaluates action identifier 136 and determines existence or non-existence of function CALCULATE.

069 In step determining 403 representation 162 of action in the second run-time environment for the identified object, interpreter 102 operates for each embodiment slightly different. In the first and second embodiments, steps 413 and 423, interpreter 102 determines that representations 162 are in string

format (cf. FIG. 5, °°). In the third embodiment, step 433, interpreter determines that the function has representation 172 (cf. FIG. 5).

070 In steps executing 404, 405, 406 and 407, interpreter 102 executes the action by using representation 162 (or 172). Interpreter 102 thereby operates for each embodiment in a slightly different manner. Common is obtaining the requested information (EXTRACT 414, PERFORM 435), converting formats (CONVERT 415, CONVERT 424, CONVERT 436) and returning messages (RETURN 417, 427, 437). Messages 112, 122, 132 to computer 901 comprise object ID 115, 125, 135 and response ID 116/118, 126/128, 136/138. The following description now conveniently splits into first, second and third embodiments.

071 First Embodiment

072 In step extracting 414, interpreter 102 extracts representation 162 of property COLOR that is identified by action ID 116 (in GET 111). So far representation 162 has the format for the second run-time environment (e.g., GREEN °°).

073 In step converting 415, interpreter 102 converts representation 162 (GREEN °°) to a further representation (GREEN °, 161) for the first run-time environment, for example, by reading from table 182 (cf. FIG. 5).

074 In step returning 417, interpreter 102 return message RESULT 112 to the first computer with object ID 115 and response ID 116/118 (cf. FIG. 4). Response ID 116/118 comprises representations for the first run-time environment (GREEN °) as property representation 118. In other words, interpreter 102 includes the extracted property into message 112 in a format

suitable for the run-time of message-receiving computer 901.

075 Second Embodiment

- 076 As property data is communicated to computer 902, extracting and converting change the order, and inserting replaces extracting.
- 077 In step converting 424, interpreter 102 converts request ID 127 (part of the action ID 126/127) to representation 162 for the second run-time environment. For example, interpreter looking up in table 182 (cf. FIG. 3) to convert RED ° to RED °°.
- 078 In step inserting 425, interpreter 102 inserts representation 162 into application 202. In the example scenario, RED ° is stored in application such that car ALPHA will actually be painted red.
- 079 In step returning 427, interpreter 102 sends message 122 to computer 901. As explained above, CONFIRM 122 has object ID 125 and response ID 126/128 with property representation 128.

080 Third Embodiment

- 081 Executing comprises converting 434, performing 435, converting 436, and returning 437 steps. Function parameters are treated similar as properties.
- 082 In step converting 434, interpreter 102 converts function ID 136 and parameter ID 137 of action ID 136/137 to function and parameter representations 172 (cf. FIG. 5) for the second run-time environment. For example, the function CALCULATE with its parameters COLOR TYPE (e.g. METALLIC), VOLUME (e.g., X) and PRICE (e.g., Y) is converted.
- 083 In step performing 435, interpreter 102 causes the identified object of application 202 to actually

provide the output parameters. The object uses function and parameter representations 172 for the second run-time environment. In the example, object A2 calculates VOLUME by multiplying the surface area of the car (e.g., square meters) with an area specific volume (e.g., liters per square meter), object A2 also calculates PRICE by multiplying VOLUME with a specific price for METALLIC (e.g., currency per liters). The parameter representations are still in the second run-time environment.

084 In step converting 436, interpreter 102 converts the parameters (that result from performing step 435) into further representations 138 for the first run-time environment. For example, interpreter 102 converts VOLUME into a numeric representation suitable for the first run-time environment (e.g., integer to real number conversion; optionally conversion of physical units); interpreter 102 converts PRICE into a numeric representation suitable for the first run-time environment, conveniently with currency conversion.

085 In step returning 437, interpreter 102 returns feedback message 132 to computer 901 with object ID 135 and response ID 136/138. Response ID 136/138 comprises the further representations for the first run-time environment.

086 Optionally, function CALCULATE uses property COLOR (cf. first and second embodiments). This is convenient, for example, when COLOR influences output parameters such as PRICE.

List of Reference Numbers

Reference	Element	Embodiment
101	communicator	
102	interpreter (CPP)	
111	GET message	first
112	RESULT message	first
115	object ID	first
116	property ID	first
116/117	action ID	first
116/118	response ID	first
117	request ID	first
118	property representation	first
121	SET message	second
122	CONFIRM message	second
125	object ID	second
126	property ID	second
126/127	action ID	second
126/128	response ID	second
127	request ID	second
128	property representation	second
131	INSTRUCT message	third
132	FEEDBACK message	third
135	object ID	third
136	function ID	third
136/137	action ID	third
136/138	response ID	third
137	parameter ID	third
138	parameter representation	third
152	object A2	
161	object representation, first RTE	
162	object representation,	

Reference	Element	Embodiment
	second RTE	
172	function and parameter representation	third
182	conversion table	
192	ERROR message	all
201	application	
202	application	
400	method and steps	
401-407	method steps	all
41x	method and steps	first
42x	method and steps	second
43x	method and steps	third
901	computer	
902	computer	
951, 952	screens	
990	network	
A1, B1, C1	objects	
A2, B2, C2	objects	
ID	identification	
RTE	run-time environment	
xx1, xx2	indices to distinguish computers	

Claims

1. A method (400, 410, 420, 430) for communication between  
a first computer (901) operating in a first object-  
oriented run-time environment and a second computer  
(902) operating in a second, different object-oriented  
run-time environment, wherein the first computer (901)  
sends a first message (GET, SET, INSTRUCT) with object  
identification (115, 125, 135) and action  
identification (116/117, 126/127, 136/137) to the  
second computer (902) and causes the second computer  
(902) to perform the following steps:
- identifying (401) an object (A2) in the second run-  
time environment according to the object  
identification (115, 125, 135);
  - verifying (402) the existence of the action  
(116/126/136) in the identified object (A2) in the  
second run-time environment;
  - determining (403) an action representation  
(162/172) of the action (116/126/136) in the second  
run-time environment for the identified object  
(A2); and



- executing (404, 405, 406, 407) the action by using the action representation (162/172), thereby returning a second message (112, 122, 132) as a confirmation message (122) to the first computer (901) with object identification (115, 125, 135) and response identification (116/118, 126/128, 136/138), executing with (a) converting (424) a request identification (127) that is part of the action identification (126/127) to a further representation (162, RED °°) for the second run-time environment by looking up in a table (182 RED ° to RED °°), and (b) inserting (425) the further representation (162, RED °) into the second application (202).

2. The method (410) of claim 1, wherein step executing further comprises:

- extracting (414) a representation (162) of a property (COLOR) that is identified by the action identification (116);
- converting (415) the representation (GREEN °°, 162) to a further representation (GREEN °, 161) for the first run-time environment; and
- returning (417) the second message as result message (112) to the first computer with object identification (115) and response identification (116, 118), the response identification (116, 118) with the representation for the first run-time environment (GREEN °).

3. The method (430) of claim 1, wherein step executing further comprises:
- converting (434) function identification and parameter identification of the action identification (136/137) to function and parameter representations (172) for the second run-time environment;
- performing (435) a function that is identified by the action identification by using the function and parameter representations (172) for the second run-time environment;
- converting (436) parameters that result from executing into further representations (136, 138) for the first run-time environment; and
- returning (437) the second message to the first computer with object identification (135) and response identification (136, 138), the response identification (136, 138) with the further representations.

4. A computer program product (102) used in a communication system of a first computer (901) with a first object-oriented run-time environment and a second computer (902) with a second, different object-oriented run-time environment, wherein the first computer (901) sends a first message (GET, SET, INSTRUCT) with object identification (115, 125, 135) and action identification (116/117, 126/127, 136/137) to the second computer (902), the computer program product (102) embodied on a carrier (972) and having computer code instructions to cause a processor (922) of the second computer to interpret the first message, the instructions comprising:
- code for identifying (401) an object (A2) in the second run-time environment according to the object identification (115, 125, 135);
  - code for verifying (402) the existence of the action (116/126/136) in the identified object (A2) in the second run-time environment;
  - code for determining (403) a representation (162/172) of the action (116/126/136) in the second run-time environment for the identified object (A2); and

code for executing (404, 405, 406, 407) the action by  
using the representation (162/172) and to return a  
second message (112, 122, 132) as confirmation  
message (122) to the first computer (901), the  
5 second message with object identification (115,  
125, 135) and response identification (116/118,  
126/128, 136/138), the code for executing with  
(a) code for converting (424) a request  
identification (127) that is part of the action  
10 identification (126/127) to a further  
representation (162, RED °°) for the second run-  
time environment by looking up in a table (182  
RED ° to RED °°), and  
(b) code for inserting (425) the further  
15 representation (162, RED °) into the second  
application (202).


5. A computer communication system with a first computer (901) operating in a first object-oriented run-time environment and a second computer (902) operating in a second, different object-oriented run-time environment, wherein the first computer (901) sends a first message (GET, SET, INSTRUCT) with object identification (115, 125, 135) and action identification (116/117, 126/127, 136/137) to the second computer (902), the system characterized in that the second computer (902) comprises:

a first module to identify (401) an object (A2) in the second run-time environment according to the object identification (115, 125, 135);

a second module to verify (402) the existence of the action (116/126/136) in the identified object (A2) in the second run-time environment;

a third module to determine (403) a representation (162/172) of the action (116/126/136) in the second run-time environment for the identified object (A2); and

a fourth module to execute (404, 405, 406, 407) the  
action by using the representation (162/172),  
thereby returning a second message (112, 122, 132)  
as confirmation message (122) to the first computer  
5 (901), the second message with object  
identification (115, 125, 135) and response  
identification (116/118, 126/128, 136/138), the  
fourth module adapted to (a) convert (424) a  
request identification (127) that is part of the  
10 action identification (126/127) to a further  
representation (162, RED °°) for the second run-  
time environment by looking up in a table (182  
RED ° to RED °°), and (b) insert (425) the further  
representation (162, RED °) into the second  
15 application (202).



**FIG. 1**  
999  
COMPUTER  
SYSTEM




FIG. 2



MESSAGE →	OBJECT ID	ACTION ID	
GET	111	115	117
		116	
	A	PROPERTY "COLOR"	REQUEST GET COLOR
SET	121	125	127
		126	
	A	PROPERTY "COLOR"	REQUEST SET TO RED °
INSTRUCT	131	135	137
		136	
	A	FUNCTION CALCULATE	PARAMETERS • METALLIC ° • X • Y

FIG. 3




FIG. 4

FIG. 5

PROPERTY	162	FUNCTION / PARAMETER	172
RED °°		CALCULATE	
YELLOW °°		• COLOR TYPE °°	
		• VOLUME °°	
		• PRICE °°	

OBJECT A2 152

FIG. 6

161	162
REPRESENTATION FIRST RTE	REPRESENTATION SECOND RTE
RED °	RED °°
YELLOW °	YELLOW °°
GREEN °	GREEN °°

182




FIG. 7




FIG. 8

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 02/09387

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06F9/46 G06F9/54

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>US 5 475 817 A (WALDO JAMES H ET AL)  12 December 1995 (1995-12-12)  column 1, line 44 -column 2, line 2  column 4, line 12 -column 5, line 62  column 6, line 52 -column 7, line 30  column 9, line 30 - line 45  column 17, line 5 - line 9</p> <p style="text-align: center;">-/--</p>	1-5



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## ° Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

13 December 2002

Date of mailing of the international search report

23/12/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk

Authorized officer

## INTERNATIONAL SEARCH REPORT

Intel al Application No

PCT/EP 02/09387

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>YI-HSIU WEI ET AL: "THE DESIGN OF A STUB GENERATOR FOR HETEROGENEOUS RPC SYSTEMS" JOURNAL OF PARALLEL AND DISTRIBUTED COMPUTING, ACADEMIC PRESS, DULUTH, MN, US, vol. 11, no. 3, 1 March 1991 (1991-03-01), pages 188-197, XP000201905  ISSN: 0743-7315  page 190, left-hand column, line 25 - line 33; figure 3  page 190, right-hand column, line 18 -page 191, left-hand column, line 9  page 191, left-hand column, line 28  -right-hand column, line 38</p>	1-5
A	<p>ANDREW D BIRRELL ET AL: "Implementing remote procedure calls" ACM TRANSACTIONS ON COMPUTER SYSTEMS, NEW YORK, NY, US, vol. 1, no. 2, 1 February 1984 (1984-02-01), pages 39-59, XP002074181  ISSN: 0734-2071  page 43, line 35 - line 46; figure 3  page 44, line 23 - line 26  page 46, line 40 -page 47, line 10</p>	1,3-5
A	<p>HUANG Y-M ET AL: "URPC: A TOOLKIT FOR PROTOTYPING REMOTE PROCEDURE CALLS" COMPUTER JOURNAL, OXFORD UNIVERSITY PRESS, SURREY, GB, vol. 39, no. 6, 1996, pages 525-540, XP000639358  ISSN: 0010-4620  page 527, right-hand column, line 16 -page 529, right-hand column, line 32</p>	1,4,5



International Application No  
PCT/EP 02/09387

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5475817	A	12-12-1995	DE 69228621 D1 22-04-1999
			DE 69228621 T2 22-07-1999
			EP 0501610 A2 02-09-1992
			JP 5181814 A 23-07-1993